



- Colour coded boots(backshells) and rings to assist in cable identification.
- In-line adaptors. Pre-wired for convenience.
- Termination tool for fast assembly of cable connectors.
- Mounting hardware.
- Metal boots(backshells) for rugged environments.

| PRODUCT - FIGURE | DRAWING | DESCRIPTION | VARIATIONS | PART NUMBER |
|------------------|--|--|--|---------------------|
| | <p>Dimensions in mm (inches)</p> <p>60.4 [2.378"]</p> <p>AMPHENOL</p> <p>Ø19.0 [Ø.748"]</p> | XLR 3 pole male to 3 pole male adapter, Pre wired, Metal Shell | Nickel Finish Black Finish | AC3M3MW AC3M3MBW |
| | <p>AMPHENOL</p> <p>Ø19.0 [Ø.748"]</p> <p>60.4 [2.378"]</p> <p>86.5 [3.406"]</p> | XLR 3 pole female to 3 pole female adapter, Pre wired, Metal Shell | Nickel Finish Black Finish | AC3F3FW AC3F3FBW |
| | <p>AMPHENOL</p> <p>Ø19.0 [Ø.748"]</p> <p>60.4 [2.378"]</p> <p>73.5 [2.892"]</p> | XLR 3 pole female to 3 pole male adapter, Pre wired, Metal Shell | Nickel Finish Black Finish | AC3F3MW AC3F3MBW |
| | <p>AMPHENOL</p> <p>Ø18.9 [Ø.744"]</p> <p>62.5 [2.461"]</p> <p>75.7 [2.980"]</p> | XLR 3 pole female to 5 pole male adapter, Pre wired, Metal Shell | Nickel Finish | AC3F5MW |
| | <p>AMPHENOL</p> <p>Ø18.9 [Ø.744"]</p> <p>62.5 [2.461"]</p> <p>75.7 [2.980"]</p> | XLR 3 pole male to 5 pole female adapter, Pre wired, Metal Shell | Nickel Finish | AC3M5FW |
| | <p>AMPHENOL</p> <p>Ø19 [Ø.748"]</p> <p>76 [2.991"]</p> | XLR 5 pole male to 5 pole male adapter, Pre wired, Metal Shell | Nickel Finish | AC5M5MW |
| | <p>792.3 [31.589"]</p> <p>100 [3.937"]</p> <p>212.0 [8.350"]</p> <p>22 [0.866"]</p> <p>74.9 [2.945"]</p> <p>2-Ø5.1 [Ø.199"]</p> <p>1-Ø6.3 [Ø.248"]</p> <p>1-Ø6.3 [Ø.248"]</p> <p>1-Ø6.3 [Ø.248"]</p> | Termination Tool | For IDC and Solder cable connectors | T2860 |
| | <p>2-Ø5.8 THRU [Ø.230"]</p> <p>1-Ø6.0 Ø.55</p> <p>22 [0.866"]</p> <p>44 [1.731"]</p> <p>49.8 [1.957"]</p> <p>70.0 [2.756"]</p> <p>91 [3.583"]</p> <p>215 [8.464"]</p> <p>Ø4.7</p> <p>END OF STROKE</p> | Termination Tool | For AC Series Right Angle cable connectors | T2880 |
| | <p>22 [0.866"]</p> <p>2-Ø5.8 THRU [Ø.230"]</p> <p>1-Ø6.0 Ø.55</p> <p>44 [1.731"]</p> <p>49.8 [1.957"]</p> <p>70.0 [2.756"]</p> <p>91 [3.583"]</p> <p>215 [8.464"]</p> <p>Ø4.7</p> <p>END OF STROKE</p> | Termination Tool | For AX Series cable connectors | T2890 |
| | <p>2.0 [0.080"]</p> <p>7.8 [0.307"]</p> <p>Ø4.3 [Ø.170"]</p> <p>ISO VIEW Ø4.0x1.5</p> <p>SELF-TAPPING SCREW WITH THREAD 2.5x1.04 AND TRI-RONDULAR CONFIGURATION</p> | A Type / C Type Connector Mounting, Self-Tapping Screw | 2.9 x 1.06 Tri-rondular | 52500002-734 |
| | <p>M2.5 x 0.45</p> <p>Ø4.50</p> <p>17</p> <p>8.0</p> | B Type Connector Mounting, Self-Tapping Screw | M2.5 | 52500005-732 |

ACC.