

Standard Data



Microphone

Cable Code	A	C	Q	MBC-20
Number of Conductors	2	2	4	2
Colour of Conductors	Blue and White			Blue and Red
Size of Conductors AWG Stranding	22 80/0.08mm		24 60/0.08mm	20 40/0.12mm
Conductor Insulation Material	PVC		PVC	PE
Strengthening Filter	Cotton			
Shield	Foil and Spiral	Foil and Braided		Spiral
Jacket Material O.D.	PVC (Black) 6.8mm +/- 0.15mm			PVC (Black) 6.5mm +/- 0.15mm
Operating Temperature	-30°C to +70°C			
Standard Packaging	100mtr plastic spool			



Instrument

Cable Code	B	IBC-20	IBC-24
Number of Conductors	1		
Colour of Conductors	Natural		
Size of Conductors AWG Stranding	20 20/0.18mm	20 40/0.12mm	24 18/0.12mm
Conductor Insulation Material	PVC	PE	
Shield	Spiral		
Jacket Material O.D.	PVC (Black) 6.0mm +/- 0.15mm	PVC (Black) 6.5mm +/- 0.15mm	PVC (Black) 6.3mm +/- 0.15mm
Operating Temperature	-30°C to +70°C		
Standard Packaging	100mtr plastic spool		



DMX / Speaker

Cable Code	D	DMX-26	SBC-12	SBC-12-4C
Number of Conductors	4	5	2	4
Colour of Conductors	Blue/Red Orange/White	Blue/Red/Orange/White	White/Black	Red/Black/White/Blue
Size of Conductors AWG Stranding	24 7/0.2mm	26	12	12
Conductor Insulation Material	FM-PE	TPOFC	CCAM	CCAM
Shield	Foil and Braided	Braided	N/A	N/A
Jacket Material O.D.	PVC (Black) 6.9mm +/- 0.3mm	PVC (Black) 6.0mm	PVC (Black) 10.2mm	PVC (Black) 11mm
Operating Temperature	-30°C to +70°C			
Standard Packaging	100mtr plastic spool			