

 $\nabla \nabla$ 

SPECIFICATIONS					
	Power Consumption	< 2 Watt			
ELECTRICAL	Power Over Ethernet (Required)	Class 1 IEEE 802.3af POE PD Compliant			
analog audio	Max Signal Level (Balanced)	+18dBu / +4dBu / 0dBu 0dBV / -10dBV			
	Impedance	150 Ohm balanced 75 Ohm unbalanced			
	Frequency Response	20Hz to 20kHz (±0.5dB)			
	Dynamic Range	>100dB			
	Signal to Noise Ratio	>100dB			
	Total Harmonic Distortion	<0.01% @ +4dBu			
Dante® audio	Sample Rate	44.1 kHz, 48 kHz (default), 96 kHz			
	Bit Depth	24 bits			
	Network Speed	100 Mbps			
	Network Interface	Latency from 1ms			
	Network Transport	Dante Audio over IP, AES67 RTP			
CLIMATIC	Protection Class	IP40			
	Operating Temperature	-5°C to +60°C (23°F to +140°F)			
MECHANICAL	Insertion and Withdrawal Force	≥10N - ≤30N			
	Weight	136g (0.299lb)			
MATERIALS	Housing	Overmolded PVC 60P Black			

/	CONNECTOR		LED STATUS			
/		FUNCTION	LEFT LED	RIGHT LED	COMMENT	
.EFT LED - /	RIGHT LED	Off	Off	Off	No Power	
		Device is booting	Solid GREEN	Solid RED		
		Slave with sync	Blinking GREEN	Solid GREEN	Normal Operation	
		Clock Master	Blinking GREEN	Blinking GREEN	Normal Operation	
		Any runtime error	Blinking GREEN	Blinking RED	Normal Operation	
		Identify	Alternating RED	Alternating RED	Blinking for 6 seconds	
		Identity	and GREEN	and GREEN	(cycle every 0.5 seconds)	
		Failsafe (bootloader) Blinking RED	Plinking DED	Blinking RED	Failsafe, Corrupt	
				Capability (red in DC)		
		Upgrade	Blinking ORANGE	Blinking ORANGE	Device is upgrading	

