Power Connectors

HPT Series



HPT Series

HPT Series connectors are suitable for AC power supply where a durable latch locking connector is required. They are rated at 16A, 250 Vac. HPT Series connectors can be connected or disconnected under load and are IP65 rated.

Features:

- 2+PE contact layout
- Quick release, vibration resistant latch lockable
- · High impact UV resistant material
- True Mains Connector with Current Breaking Capacity (CBC)
- 16A current rating (20A USA)
- Industry standard mating interface
- IP65 rated
- Patent Protected*
- UL498 certified
- UL50E enclosure type 4 (when mated or in combination with protective caps)



Power Connectors

HPT Series

PRODUCT - FIGURE	DRAWING	Dimensions in mm (inches)	DESCRIPTION	COLOUR	PART NUMBER
	Ø3.0 [Ø0.12]	8 (1.21)	Protective sealing cap with stainless steel lanyard to suit HPT-3-MD / HPT-3-MDW	Black	HPT-CAPM
0.0	03.0 (00.12)	0.4 [1.59]	Protective sealing cap with stainless steel lanyard to suit HPT-3-FD / HPT-3-FDW	Black	HPT-CAPF
	Ø3.0 (Ø0.12)	86.0 [2.80]	Protective sealing cap with stainless steel lanyard to suit HPT-3-CC	Black	HPT-CAPD
	74	93.2 [00.13]	Protective Self-closing sealing cap with stainless steel spring to suit HPT-3-MD / HPT-3-MDW	Black	HPT-CAPSM
	[96:1] 6:69	23.2 [20.13]	Protective Self-closing sealing cap with stainless steel spring to suit HPT-3-FD / HPT-3-FDW	Black	HPT-CAPSF
	[98] 1 687	03.2 (00.13) 67.1 [2.64]	Protective Self-closing sealing cap with stainless steel spring to suit HPT-3-CC	Black	HPT-CAPSD
	28.2 [1.11	21.0 [0.83]	Cable connector backshell lock release tool	Black	HPT-RT